


## PROTEC BRUSH

Brush sealant



### DESCRIPTION

Single-component, snap-on, repaintable, thixotropic-looking, satiny elastic sealant. Useful for sealing new or old welded edges, joints and similar in the automotive, construction and metal industry, containers, ventilation systems and machinery in general.

PROTEC **BRUSH** remains permanently flexible after drying and therefore counteracts vibrations on moving sealed parts.

### COLORS

PROTEC **BRUSH**

7470

### SURFACE PREPARATION

Surfaces must be clean, dry and free of dust, grease and rust. For better adhesiveness of the product, peeling parts, dirt and rust should be removed.

### USE

Apply 1 or 2 coats using a brush to achieve a thickness of up to 300 dry microns.

### APPLICATION

	<p>Number of Coats Dry thickness <math>\mu\text{m}</math></p>	<p>1 o 2 coats 300</p>
	<p>Drying Time 20°C</p>	<p>30 -60'</p>

Can be repainted after 30 min. although it is advisable to wait 24 hours.

---

**SAFETY INSTRUCTIONS** 

The use of appropriate personal protective equipment is recommended during application, to prevent the irritation of the respiratory tract, skin and eyes. For professional use only.

---

**STORAGE** 

Keep in a tightly covered container, in a dry and ventilated place, avoiding direct exposure to sunlight. Temperature above 5°C is recommended, between 15 and 30°C optimal.

---

**VOC** 

The VOC content of PROTEC **BRUSH** is a maximum of 840 g/l in compliance with European regulation 2004/42/EC IIB(E)(840) <840 g/l.

---

The information contained in this Technical Specification Sheet is based on the knowledge and experience of the BESA technical department, and with it it's intended to advice and inform, being the responsibility of the user to take the necessary measures to guarantee the intended purpose of the product. **FOR PROFESSIONAL USE ONLY.**

---